

| Preflight | | |
|---------------------|--------------|--|
| Interior | | |
| Garmin D2 Charlie 3 | Fly Mode | |
| Passengers | Brief | |
| Circuit Breakers | In | |
| Alternate Static | Check Closed | |

| S | tart |
|-------------------|-------------|
| Seat Track & Back | Locked |
| Brakes | Pedal Test |
| Avionics | Off |
| Auto-pilot | Off |
| Carb Heat | Off |
| Cowl Flaps | Open |
| Beacon | On |
| Mixture | Full Rich |
| Prop | High RPM |
| Throttle | Slight |
| Prime | As Required |
| Brakes | Set |
| Prop | Clear |
| Master | On |
| Mags | Start |
| Oil Pressure | Check |
| Lights | As Required |
| Mixture | As Required |
| Taxi | |

| Up As Required |
|-------------------|
| As Required |
| 710 Neganea |
| On & Set |
| Alt + Squawk |
| Set |
| Test |
| |
| As Required |
| Test |
| Test |
| Test |
| Test |
| Mag Check |
| |

| Run-up | | |
|-----------------|----------------|--|
| Brakes | Set | |
| Fuel | Both | |
| Trim | Takeoff | |
| Flight Controls | Free & Correct | |
| Instruments | Check | |
| Mixture | Best Power | |
| | | |

| Primer | In & Locked |
|---------------------|---------------------|
| 1700 RPM | Set |
| Mags (Right & Left) | Test |
| Comments | |
| +/-50 RPM | |
| Prop | Cycle |
| Carb Heat | Test for 10 seconds |
| Vacuum | Check |
| Amps & Volts | Check |
| Oil Pressure | Check |
| Oil Temp | Check |
| Idle | Check Closed |
| Throttle Friction | Lock |

| Inflight | | |
|----------------------------------|--------------------|--|
| Pre-Takeoff | | |
| Flaps | 0° - 20° | |
| Prop | High RPM | |
| Mixture | Best Power | |
| Carb Heat | Off or As Required | |
| Pitot Heat | As Required | |
| Heading Indicator To Compass Set | | |
| Doors | Close & Lock | |
| Windows | Close & Lock | |
| AC | Off | |
| Transponder | Alt + Squawk | |
| Landing Light | On | |
| Strobes | On | |
| Time | Note | |
| Brakes | Release | |
| Abort Plan | Ready !! | |
| Garmin D2 Charlie | Start | |
| _ | 1 ((| |

| Takeoff | |
|----------------|--|
| 2600 RPM (Max) | |
| Check | |
| Check | |
| 52 KIAS | |
| 77 KIAS | |
| Up | |
| | |

| Climb | | |
|----------------------|-------------|--|
| Climb | 87-96 KIAS | |
| Throttle | 23" MP | |
| Prop | 2450 RPM | |
| Mixture | As Required | |
| Cowl Flaps | Open | |
| Instruments | Check | |
| Taxi & Landing Light | Off | |
| Flight Plan | Open | |
| | | |

| Cruise | |
|-----------------------------|--------|
| Throttle | Set |
| Prop | Set |
| Mixture | Set |
| Instruments | Check |
| Cowl Flaps | Close |
| Heading Indicator To Compas | ss Set |
| 7500' 54% 121 KIAS | |
| 19"-2200 RPM-10.2 GPH | |
| 7500' 62% 129 KIAS | |
| 20"-2300RPM-11.6GPH | |
| 7500' 71% 136 KIAS | |
| 21"-2450 RPM-13.1 GPH | |

| Descent | |
|-------------|----------------------|
| Throttle | Manifold As Required |
| Mixture | Richen |
| Cowl Flaps | Close |
| Fuel | Both |
| Carb Heat | As Required |
| ATIS & AWOS | Note |
| Altimeter | Set |
| Instruments | Check |

Heading Indicator To Compass Set

| Pre-Landing | |
|---------------------|-------------|
| Landing Light | On |
| Auto-pilot | Off |
| AC | Off |
| Seat Belt & Harness | Secure |
| Mixture | Best Power |
| Carb Heat | On |
| Fuel | Both |
| Flaps | As Required |

| Landing | |
|---------|---|
| Flaps | 40° Or As Required |
| Prop | High RPM |
| Speed | 70 KIAS |
| GUMPS | Check Fuel Valve, Mixture Full, Prop Set, Seatbelts & Switches |

| Go-Around | | |
|---------------------|----------------|--|
| Trim | Takeoff | |
| Power | Full | |
| Carb Heat | Off | |
| Positive Rate Climb | Confirm | |
| Flaps Up | Retract Slowly | |
| Cowl Flaps | Open | |

Postflight

| After Landing | | |
|---------------|--------------|--|
| Flaps | Up | |
| Carb Heat | Off | |
| Cowl Flaps | Open | |
| Strobes | Off | |
| Landing Light | Off | |
| Taxi Light | As Required | |
| Pitot Heat | Off | |
| Trim | Takeoff | |
| Transponder | Alt + Squawk | |

| Пипоропист | 7111 · Oquavik | |
|-------------------|----------------|--|
| | Securing | |
| E.L.T. | Verify Silent | |
| Lights | Off | |
| Garmin D2 Charlie | Stop | |
| Avionics | Off | |
| Mixture | Full Lean | |
| Mags | Off | |
| Master | Off | |
| Fuel | Left or Right | |
| Cowl Flaps | Closed | |
| Control Lock | Install | |
| Chocks | In | |
| Tie Downs | Secure | |
| Pitot Cover | Install | |
| Baggage Door | Secure | |
| Cabin Doors | Secure | |
| Flight Plan | Close | |
| Be Safe!!! | | |

| Safe Airspeed 70 KIAS Off Full Lean & Idle Cutoff Down Off Unlatch ss Inflight Keep Aircraft Control 70 KIAS On Direction & Velocity Select Full Rich Check Switch on Both Locked (Try Reprime) Check All |
|---|
| 70 KIAS Off Full Lean & Idle Cutoff Down Off Unlatch ss Inflight Keep Aircraft Control 70 KIAS On Direction & Velocity Select Full Rich Check Switch on Both Locked (Try Reprime) |
| 70 KIAS Off Full Lean & Idle Cutoff Down Off Unlatch ss Inflight Keep Aircraft Control 70 KIAS On Direction & Velocity Select Full Rich Check Switch on Both Locked (Try Reprime) |
| Off Full Lean & Idle Cutoff Down Off Unlatch ss Inflight Keep Aircraft Control 70 KIAS On Direction & Velocity Select Full Rich Check Switch on Both Locked (Try Reprime) |
| Full Lean & Idle Cutoff Down Off Unlatch ss Inflight Keep Aircraft Control 70 KIAS On Direction & Velocity Select Full Rich Check Switch on Both Locked (Try Reprime) |
| Down Off Unlatch ss Inflight Keep Aircraft Control 70 KIAS On Direction & Velocity Select Full Rich Check Switch on Both Locked (Try Reprime) |
| Off Unlatch ss Inflight Keep Aircraft Control 70 KIAS On Direction & Velocity Select Full Rich Check Switch on Both Locked (Try Reprime) |
| Unlatch ss Inflight Keep Aircraft Control 70 KIAS On Direction & Velocity Select Full Rich Check Switch on Both Locked (Try Reprime) |
| ss Inflight Keep Aircraft Control 70 KIAS On Direction & Velocity Select Full Rich Check Switch on Both Locked (Try Reprime) |
| Keep Aircraft Control 70 KIAS On Direction & Velocity Select Full Rich Check Switch on Both Locked (Try Reprime) |
| 70 KIAS On Direction & Velocity Select Full Rich Check Switch on Both Locked (Try Reprime) |
| On Direction & Velocity Select Full Rich Check Switch on Both Locked (Try Reprime) |
| Direction & Velocity Select Full Rich Check Switch on Both Locked (Try Reprime) |
| Select Full Rich Check Switch on Both Locked (Try Reprime) |
| Full Rich Check Switch on Both Locked (Try Reprime) |
| Check Switch on Both Locked (Try Reprime) |
| Locked (Try Reprime) |
| , , , , |
| Check All |
| |
| On |
| t with Time |
| 70 KIAS |
| Low RPM & Full Aft |
| 7700 |
| TWR, APP, 121.5 |
| Off |
| Full Lean & Idle Cutoff |
| Secure |
| Full Or As Needed |
| Off |
| Doors |
| Use Soft Objects |
| |
| |

| Electrical Fire | | |
|-------------------------|-------------------|--|
| All Electrical & Master | Off (Mags On) | |
| Cabin Heat & Air | Off | |
| If Fire Out | | |
| Master | On If Critical | |
| Vents | Open | |
| Electrical | On One At A Time | |
| Circuit Breaker | Reset If Critical | |

| Engine Fire On Startup | | |
|------------------------|-------------------------|--|
| Engine | Continue Cranking | |
| If Start | | |
| Run | Only A Few Seconds | |
| Then | Shutdown & Inspect | |
| If No Start | | |
| Mixture | Full Lean & Idle Cutoff | |
| Fuel Selector | Off | |
| Throttle | Full Open | |
| Continue Cranking Eng | For A Few Seconds | |
| Master & Mags | Off | |
| Evacuate | A.S.A.P. | |
| Fire Extinguisher | As Required | |
| Engine Fire Inflight | | |

| Full Lean & Idle Cutoff |
|-------------------------|
| Off |
| Off |
| Off Except Ovrhd Vents |
| To Extinguish |
| A.S.A.P. |
| |

| lcing | | |
|----------------------|----------------------|--|
| Pitot Heat | On | |
| Carb Heat | On | |
| Cabin Heat & Defrost | Maximum | |
| Strongly Consider | 180° Turn | |
| Change Altitude | Higher or Lower | |
| Engine & Prop Speed | Increase | |
| Flaps | Not Rec. For Landing | |
| Land Faster | As Needed | |

| Excess Charge | | |
|--------------------------|---------------|--|
| ALT CB | Pull | |
| Non-Essential Electrical | Off | |
| Master | Off (Mags On) | |
| Land A.S.A.P. | BATT only | |
| | | |

| Low Voltage | | |
|--------------------------|-------------|--|
| Avionics | Off | |
| ALT CB | In | |
| Master | Off Then On | |
| Check Volt Light | Off | |
| If Low Voltage Again | | |
| ALT | Off | |
| Non-Essential Electrical | Off | |
| Land A.S.A.P. | BATT only | |

| Radio Out | | |
|--------------------|-------------|--|
| Circuit Breaker | Check | |
| Volume | Check | |
| ALT Switch | Recycle | |
| IFR & Still Out | Squawk 7600 | |
| VFR B,C,D Airspace | Squawk 7600 | |